

Challenger 2008-09 Louver Installation (tape)

Before you start the installation, you must ensure that the temperature of the room is at least 60⁰ F (18⁰C). Never touch the foam tape with your fingers.

Approximate installation time: 15 minutes.

Step 1	Center the louver on the windshield (see picture below). Both sides of the louver must be sitting on the body of the car. Make sure the strap hinges are resting on the roof. Verify that the trunk opens freely and if not, move the louver upwards slightly. Open the trunk again for a final verification.
Step 2	Stick masking tape around the strap hinges and around the pins as reference points.
Step 3	Remove the louver from the car. Scrub the areas where the strap hinges and pins will be positioned (area inside the masking tape) with the pad provided in the installation bag. This step is required to remove any wax or similar substance that would prevent adhesion of the foam tape.
Step 4	Clean the areas that you just scrubbed with an alcohol based product. Let dry for 5 minutes to ensure it is completely free of any moisture.
Step 5	Place the louver back on the car using the masking tapes to position it properly. Remove the film from the foam tape under the strap hinges and stick them to the roof. Repeat the operation for the pins.
Step 6	Detach the clips from the pins to free up the louver in order to remove any pressure on the pins. Raise the lower end of the louver (about 6 inches) and support the louver in this position with a towel or any object that will not damage the windshield. This will maximize the adhesion of the foam tape. Remove the masking tapes. After 72 hours, attach the clips to the louver to complete installation.
Step 7	You must wait 72 hours before you drive your car with the louver. This time is required for the tape to reach full adhesion.
Step 8	Hit the road and enjoy your distinctive louver!

N.B. Never lift the louver higher than the roof of the car. The pressure this position could generate could damage the roof.



Limited Parts Industries Return Policy and Warranty

Returns

We take pride in your satisfaction. Our goal is to get your order complete, undamaged and fit for its purpose. As a result, products can be returned within 30 days of shipment as long as they are unused, uninstalled and in new and saleable condition.

1. You must call us first to get an authorization to return the product.
2. Returned products need to be in their original packaging with all hardware parts and instructions included. Send the product back prepaid as **no C.O.D** returns will be accepted.

All returns of non-damaged or non-defective parts are subject to a 15 % restocking fee.

Damaged Merchandise (during shipment)

Upon receiving your order, open the crate(s) immediately and thoroughly inspect the contents. If any package arrives and shows signs of external damage, simply refuse the shipment. The delivery service will then return the crate(s) to us and we will file claim with the carrier. If you already accepted the shipment, don't throw anything away, please keep all packaging materials should the carrier wish to inspect them. Contact us within seven (7) days and we will give you complete instructions on how to handle the situation.

Once the claim is filed, we will then replace the product.

Limited One (1) year warranty

We offers a one (1) year warranty after shipment on material and/or manufacturing defects on our products as long as the instructions for installation where followed. This warranty does not include consequential nor incidental damages caused by the product. In order to get service under this warranty, contact the seller to receive instructions on how to proceed. We will replace the defective part.

This warranty does not cover the discoloration of a louver as a result of using abrasive cleansing products. This warranty does not apply if the car on which one of our products is installed is used mainly for drag racing.

This warranty gives you specific legal rights, and you may also have other rights which vary from state to state (or province).